

PLAZA SERIES™

Interlocking Concrete Pavement System (ICP)

Durable Flexible Pavement System

Style & Dimensions

Plaza Rectangle™

60mm Height & 80mm Height
160mm x 240mm
Approximate 6 1/4" x 9 3/8"
(60mm PSF = 2.46 stones @ 28#)
(80mm PSF = 2.46 Stones @ 35.5#)



Plaza Square™

60mm Height & 80mm Height
160mm x 160mm
Approximate 6 1/4" x 6 1/4"
(60mm PSF = 3.69 stones @ 28#)
(80mm PSF = 3.69 Stones @ 35.5#)



Benefits of ICP

- Flexible system, does not crack or heave in cold climates
- Easier maintenance to the pavement and utilities underneath
- Achieve endless design possibilities with different shapes, textures, colors and laying patterns
- Use pavers to delineate lines and spaces to eliminate the need to maintain paint
- Suitable for a range of applications: plazas, walkways, driveways, roads, etc.
- Borgert pavers are made with granite, creating a dense, resistant wearing course

PLAZA SERIES™

Composition and Manufacture

Pavers exceed industry standards: 8,000 psi - 5% absorption

Meets or exceeds ASTM C-936 and freeze-thaw testing per section 8 of ASTM C-67

Manufactured with type A aggregates

Associated with a range of LEED credits

ADA Compliant

Written detailed specification information is available, call or visit our website.



Edge restraint detail provided based on application.

Laying Patterns

