## HOLLAND STONE<sup>TM</sup>





## **DURABLE FLEXIBLE PAVEMENT SYSTEM**

STYLE	CODE	DIMENSIONS	BANDS	CUBES
Holland Stone™ 4" x 8"	4HS	100mm x 200mm x 60mm Approximate 3 <sup>7</sup> / <sub>8</sub> " x 7 <sup>7</sup> / <sub>8</sub> " x 2 <sup>3</sup> / <sub>8</sub> " (PSF = 4.5 stones @ 28#)	15.7 SF 440# (72 stones)	94 SF 2640# (6 bands)

#### **COMPOSITION & MANUFACTURE -**

#### **Typical Cross Section of Concrete Paving Stone**



Edge restraint detail provided based on application.

**Borgert Pavers** 

Bedding Sand 1" Thick (ASTM C33)

Compacted Aggregate Base Class 2 or Class 5

(Thickness depends on soil condition and application)

Prior to screeding the bedding sand, the base surface tolerance must not exceed +/-1/4 in.(+/-6mm) over a 10gt. (3m) straight edge.

Compacted Soil Subgrade

- Pavers exceed industry standards: 8,000 psi 5% absorption
- Meets or exceeds ASTM C-936 and freeze-thaw testing per section 8 of ASTM C-67
- Manufactured with type A aggregates
- Associated with a range of LEED credits
- ADA Compliant

Written detailed specification information is available, call or visit our website at borgertproducts.com.

# HOLLAND STONE<sup>TM</sup>





## **BENEFITS OF ICP**

- Flexible system, does not crack or heave in cold climates
- Easier maintenance to the pavement and utilities underneath
- Achieve endless design possibilities with different shapes, textures, colors and laying patterns
- Use pavers to delineate lines and spaces to eliminate the need to maintain paint
- Suitable for a range of applications: plazas, walkways, driveways, roads, etc.
- Borgert pavers are made with granite, creating a dense, resistant wearing course

## LAYING PATTERNS -

